

Frequently Asked Questions: Steam Showers

What thickness of glass is used?

1/4" (6mm) in framed system - 3/8"(10mm) in frameless glass systems.

What type of glass is used?

Tempered safety glass

Are there different colors or patterns of glass used?

Clear glass is most commonly used. Frosted or sandblasted glass is popular too.

What size doors are available?

The doors are made to measure, but are generally under 28" (711mm) wide

How do the doors seal?

Framed doors have magnetic seals; frameless doors are equipped with clear vinyl gaskets.

How long does it take before it is received?

Approximately 3 weeks from date of measurement.

When can you measure?

Only when all the tile or marble has been installed for frameless steam doors.

We know what the finished size will be, why can't you order the steam door based upon these measurements?

There is very little adjustment on custom enclosures. The glass is cut to fit precisely. It is very risky to order the glass prior to finishing the enclosure.

Can the doors be installed to swing in to the shower?

Only frameless doors which have double acting hinges can swing both inwards and outwards. This is a great advantage in confined areas where there is insufficient room to open the door outwards. Framed doors swing outwards only.

What color of hinges is available?

Chrome/Brass/White/Brushed Nickel and many other colors available.

How is the pricing calculated?

All custom projects are quoted on an individual basis.

Can you give me a ball park price on a standard door 24" wide x 78" high

Please email, fax or call 1-866-789-3338 for quotations.